



### Main

|                              |  |
|------------------------------|--|
| Range                        | Acti 9   |
| Device short name            | IATLc+S  |
| Product or component type    | Centralized control and remote indication auxiliary  |
| Signal contacts composition  | 1 C/O  |
| Signalling circuit voltage   | 24 V AC/DC : 10 mA<br>12...240 V AC : 50/60 Hz 6 A<br>12...24 V DC : 6 A<br>15...240 V AC : 50/60 Hz 2 A<br>13...24 V DC : 2 A |
| [Uc] control circuit voltage | 24...240 V AC 50/60 Hz   |


### Complementary

|                         |  |
|-------------------------|--|
| Mounting mode           | Fixed, on right side of TL   |
| Mounting support        | DIN rail   |
| 9 mm pitches            | 2  |
| Height                  | 81 mm  |
| Width                   | 18 mm  |
| Depth                   | 71 mm  |
| Colour                  | White  |
| Connections - terminals | Tunnel type terminals rigid cable(s) 0.5...4 mm <sup>2</sup><br>Tunnel type terminals rigid cable(s) with cable end 0.5...4 mm <sup>2</sup><br>Tunnel type terminals flexible cable(s) 1...4 mm <sup>2</sup><br>Tunnel type terminals flexible cable(s) with cable end 1...4 mm <sup>2</sup> |
| Wire stripping length   | 11 mm  |
| Tightening torque       | 1 N.m  |
| Range compatibility     | Acti 9 iTL<br>Acti 9 iTLi<br>Acti 9 iTLs   |
| Product compatibility   | ITL (32 A)<br>ITL (16 A)   |

## Environment

|                                       |              |
|---------------------------------------|--------------|
| Tropicalisation                       | 2            |
| Relative humidity                     | 95 % (55 °C) |
| Ambient air temperature for operation | -20...50 °C  |
| Ambient air temperature for storage   | -40...70 °C  |

## Offer Sustainability

|                                  |   |
|----------------------------------|---|
| Sustainable offer status         | Green Premium product   |
| RoHS (date code: YYWW)           | Compliant - since 0901 - Schneider Electric declaration of conformity<br><a href="#"> Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold<br><a href="#">Reference not containing SVHC above the threshold</a>  |
| Product environmental profile    | Available   |
| Product end of life instructions | Need no specific recycling operations   |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|