

VZ1L018UM20

line choke - 2 mH - 18 A - 1 phase - 30 W - for
variable speed drive

pdf.price.label* : 96.00 GBP



Main

Range of product	Altivar
Product or component type	Line choke
Product compatibility	ATV312HU11M2 - line choke - 1 per drive ATV312HU15M2 - line choke - 1 per drive ATV312HU22M2 - line choke - 1 per drive ATV31CU11M2 - line choke - 1 per drive ATV31CU15M2 - line choke - 1 per drive ATV31CU22M2 - line choke - 1 per drive ATV32HU11M2 - line choke - 1 per drive ATV32HU15M2 - line choke - 1 per drive ATV32HU22M2 - line choke - 1 per drive LXM05D17F1 - line choke - 1 per drive LXM05D17M2 - line choke - 1 per drive LXM05D28F1 - line choke - 1 per drive LXM05D28M2 - line choke - 1 per drive LXM32.D18M2 - line choke - 1 per drive LXM32.D30M2 - line choke - 1 per drive LXM32.U90M2 - line choke - 1 per drive Variable speed drive ATV320 motor : 1.1 kW 200...240 V - single phase - line choke - 1 per drive Variable speed drive ATV320 motor : 1.5 kW 200...240 V - single phase - line choke - 1 per drive Variable speed drive ATV320 motor : 2.2 kW 200...240 V - single phase - line choke - 1 per drive
Network number of phases	Single phase
Range compatibility	Altivar 32 Altivar Machine ATV320 Altivar 31C Altivar 312 Solar Altivar 312 Lexium 32 Lexium 05
Device application	Reduction of current harmonics
Value of inductance	2 mH
[In] rated current	18 A
Thermal losses	30 W

Complementary

Supply frequency	50...60 Hz
Voltage drop at rated load	3...5 %
Product weight	1.99 kg
Width	85 mm
Height	120 mm
Depth	105 mm

Environment

Standards	IEC 60076 (with HD398) EN 50178 VDE 0160 level 1
IP degree of protection	IP00 (choke) IP20 (terminals)

Contractual warranty

Warranty period	18 months
-----------------	-----------